



## PRODUCT INFORMATION

# SUNOCO Ecotac

- Description** Biodegradable chainsaw oil with excellent lubricating tackiness and wear reducing properties. Based on vegetable oils with stickiness properties.
- Application** Essentially for chain lubrication of motorized saw equipment. However, application may be considered everywhere a tacky biodegradable lubricant is required, subjected to temperatures of maximum 60°C. Especially recommended wherever spilling in nature is likely or unavoidable.
- Specifications**
- Low pour point and excellent low temperature fluidity.
  - Light coloured lubricant.
  - Excellent tackiness.
  - Biodegradability according OECD 301B: 75,9%
- Properties**
- Biologically degradable lubricant.
  - Excellent lubricating properties.
  - Low oil throw-off due to high tackiness.
  - Low chain wear.
  - Excellent fluidity at low temperatures.
  - No oil hardening during equipment storage (in winter season) rendering permanent serviceability.
  - Mineral oil compatible allowing immediate switch-over from classic type saw lubes without disassembling, cleaning or observing any other special precautions.

### Typical analysis

Density at 15 °C	0.918
Viscosity 40 °C / cSt	68
Viscosity 100 °C / cSt	14.3
Viscosity Index	238
Flash Point °C	250
Pour Point °C	-27